

FINAL POST-LAYING CLEANING

After laying the tiles, following all the rules of professional workmanship, it is important to proceed with the first special cleaning, which must be carried out while the grouting mix is still wet, when the residues, therefore, are still easy to remove. After slightly dampening the wall covering and/or flooring, remove everything with a damp sponge. This serves the dual purpose of cleaning and, at the same time, smoothing off and levelling the laying joint perfectly. Now, rinse several times with clean water until the tiles are perfectly clean.

END-OF-JOB CLEANING PRODUCTS

If you intend to use products for cleaning up and coating the tiling at the end of the job, remember never to use acidic detergents. Clean the surface by washing it with a water solution obtained by diluting FILACLEANER or FABER WAX REMOVER. Use a sponge or a white pad for the first wash, then rinse thoroughly with water.

STAIN PROTECTION TREATMENT

Once the surface is dry, brush on a coat of FILA MP/90 or FABER CRAQUELÉ PROTECTOR. Apply the product a little at a time, making sure you spread it evenly and well. After applying the primer, wait 4-6 hours before removing the surplus that has formed using either a dry cloth or, at the most, one that has been dampened.

DAILY CLEANING AND MAINTENANCE

We strongly advise against the use of HARSH PRODUCTS SUCH AS ACIDS AND OTHER SUBSTANCES OR ABRASIVE TOOLS (LIME SCALE REMOVAL PRODUCTS, ABRASIVE SPONGES, ETC.). For the daily cleaning of Ceramica Senio wall and floor tiles. Likewise, we recommend you use the standard neutral-based products available in the shops. Please be informed that if the Ceramica Senio tiles with crackle texture come into contact with dirty or greasy water, substances or materials, the crackle effect on the surface could be ruined.

PERIODIC MAINTENANCE

For surfaces which are particularly at risk of staining, such as kitchen walls and tops, we recommend you renew the STAIN PROTECTION TREATMENT every 2-3 years. Before carrying out this maintenance, we advise you to clean the surface with FILA CLEANER or FABER WAX REMOVER. After the first wash, and when the surface is dry, brush on a coat of FILA MP/90 or FABER CRAQUELÉ PROTECTOR.

EXTRAORDINARY MAINTENANCE

If the material has been cleaned with a pH acid detergent and, after the cleaning, it is possible to see some iridescent or aggressive effect on the glaze, we recommend the use of FABER polishing cream to recover. If the material has been affected deeply by the acid corrosion, we recommend to use FABER polishing cream with a Roto-Orbital machine. Once the cleaning is over, it is recommended to wash the surface with clean water.

WARNING

Info sheet produced in association with Faber Chimica srl and Fila Industria Chimica spa. For further information of a technical nature, please contact Faber Chimica srl directly calling phone number +39 0732 627178 or visiting web site www.faberchimica.com, or Fila Industria Chimica spa directly calling phone number +39 049 9467300 or visiting web site www.filachim.com. Though the information contained in this info sheet derives from vast technical and operative experience and research, it should not be considered as binding given that operative conditions cannot be controlled by our company. Ceramica Senio therefore declines all liability deriving from the use of this information and these suggestions.

MORE INFO:



Town & Country Surfaces
230 Fifth Avenue
Suite 1714
New York NY 10001

General Inquiries:
info@tncsurfaces.com
Phone: 212-679-0312