

# Technical Specifications



**Technical features for Dry-Pressed ceramic tiles with water absorption BIII (Eb >10%)**  
 Características técnicas para las baldosas cerámicas prensadas en seco del grupo BIII (Eb >10%)

| FEATURES / CARACTERÍSTICAS               | SPECIFICATION / ESPECIFICACIÓN  | NORMA                    |
|--|---|--------------------------|
| Dimensional Features                     | 107 mm +/- 0,75 mm x 538,5 mm +/- 0,5 %   | UNE-EN ISO 10545-2:1998  |
| Water absorption                         | $E_b > 10\%$  | UNE-EN ISO 10545-3:1997  |
| Modulus of rupture and breaking strength | Thickness $\leq 7,5$ mm mínimo 15 N/mm <sup>2</sup><br>Thickness $> 7,5$ mm mínimo 12 N/mm <sup>2</sup> | UNE-EN ISO 10545-4:2012  |
| Crazing resistance                       | Pass  | UNE-EN ISO 10545-11:1997 |
| Household products resistance            | GA  | UNE-EN ISO 10545-13:1998 |
| Chemical resistance                      | GHA   | UNE-EN ISO 10545-13:1998 |
| Stain resistance                         | Class 5   | UNE-EN ISO 10545-14:1998 |
| Tone variation                           | V1  | -                        |
| White body                               | -   | -                        |

|         |             |              | LB        | FT2                   |                | FT2                     |
|---------|-------------|--------------|-----------|-----------------------|----------------|-------------------------|
| Model   | Format (in) | Pieces / Box | Lb/ box   | sq ft / Box           | Boxes / Pallet | sq ft / Pallet          |
| MELANGE | 4.2"x21.3"  | 10           | 21.561 lb | 6.232 ft <sup>2</sup> | 91             | 567.112 ft <sup>2</sup> |

**MORE INFO:**



**Town & Country Surfaces**  
 230 Fifth Avenue  
 Suite 1714  
 New York NY 10001  
**General Inquiries:**  
 info@tncsurfaces.com  
 Phone: 212-679-0312

