



The Uno glass series was built with a palette and style inspired by the great modern architects: Gehry, Hadid, and Mies van der Rohe. The meticulously curated colors and shapes provide a series of versatile design components for a multitude of spaces. Use modestly, or combine elements to create graphic appeal.



RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	Yes A	Yes ^
Fireplace/Cooktop Surround	Yes *	Steam Shower	Yes A	N/A
Shower Wall	Yes	Light Residential	Yes A	No
Steam Shower	Yes	Residential	No	No
Exterior Wall	Yes	Note: Silk finish is recommended for floor/foot traffic applications and		
Pool, Spa or Water Feature (fully submerged)	No **	usage.		

PRC	DOUCT SPECS			
Size (Dimension In Nominal Size)	Coverage	Packaging (Per Box)		Stan
½ x 1 Mini Brick	0.93 (SF/ Sheet)	5 Sheets/4.65 SF	Breaking Strength	
1 x 1 Mosaic 3 x	1.10 (SF/ Sheet)	5 Sheets/5.50 SF	Water Absorption	
6 3 x 9 3 x 12	8.60 (PCs/SF)	24 Pieces/2.784 SF	Chemical Resistance	
Falling Water	5.68 (PCs/SF)	18 Pieces/3.168 SF	Freeze/Thaw	
Flat Bar	4.27 (PCs/ SF)	12 Pieces/2.808 SF	Thermal Shock	
	0.99 (SF/ Sheet)	5 Sheets/4.95 SF		
(½ x 5 ³ / ₄ ")		100 Pieces/Box	Cia a a consisti a management	
Shade Variation	Grout Joint Recommendation		Since variations are common selection be made from an a	

MORE INFO:

Town & Country Surfaces 230 Fifth Avenue **Suite 1714** New York NY 10001

V1 - V2 Slight Variation

General Inquiries:

info@tncsurfaces.com Phone: 212-679-0312



1/8" (3 mm)

* Acceptable for use near open flame or heat source; However it is NOT considered 'Fire Glass'.

- ** All Uno series tiles are not suitable for usage in pools, spas, or water features.
- ▲ Size and Pattern Limitations: 3 x 6", 3 x 9", 3 x 12" and Falling Water pattern are NOT recommended for use on floors.

TESTING

Standards Methods					
Breaking Strength	ASTM C-648	>650 PSI			
Water Absorption	ASTM C-373	Impervious < 0.01%			
Chemical Resistance	ASTM C-650	Unaffected			
Freeze/Thaw	ASTM C-1026	Unaffected			
Thermal Shock	ASTM C-484	Passed			

NOTES

on in artistic glass tile, we recommend final actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of Uno tile can be done with a light duty nonabrasive, close to neutral pH detergent cleaner.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.