

HUE

Porcelain Tiles
ISO 13006 Annex G - UNI EN 14411 Annex G - Bla UGL
ANSI A137.1 - CLASS P1



TECHNICAL FEATURES		STANDARD	VALUE		
	Water Absorption	ASTM C373	Compliant		
	Resistance Flexion	SPESSORE	6,5 mm	9,5 mm	
		UNI EN ISO 10545/4	≥ 35 N/mm2	≥ 45 N/mm2	
	Breakingstrength	UNI EN ISO 10545/4	≥ 700 N	≥ 2000 N	
		ASTM C648	≥ 175 lbf	≥ 400 lbf	
	Frost Resistance	UNI EN ISO 10545/12	Conforme		
		ASTM C1026	Unaffected		
	Chemical Resistance	UNI EN ISO 10545/13	A - LA - HA		
		ASTM C-650	Unaffected		
Chemical resistance to high and low acid and basic concentrations					
	Stain Resistance	UNI EN ISO 10545/14	5 Class A		
		ASTM C1378	NATURAL		
	Slip Resistance		E	SILKTECH	SILKTECH PLUS
		DIN EN 16165 Annex B DIN EN 16165 Annex A	R9	R10	R11
		ANSI A326.3:2017 DCOF	-	B (A+B)	B (A+B)
			WET ≥ 0,42	WET ≥ 0,50	WET ≥ 0,65
		B.C.R.A. D.M. N. 236 14/6/89	> 0,40	> 0,40	> 0,40
		AS 4588-2013 Anexo A	-	P3	P4
		PENDOLO BS 7976 BSEN13036	-	> 36	> 36
		4: 2011 Pendulum testers	-	Low Slip potential	Low Slip potential
				2	
		UNE 41901:2017 EX DB SUA (actual)	-	3	

P For further information on technical specifications, please consult our up-dated general catalogue



MORE INFO:



Town & Country Surfaces
230 Fifth Avenue
Suite 1714
New York NY 10001

General Inquiries:
info@tncsurfaces.com
Phone: 212-679-0312