

T-938 Bellagio - Technical information

Collection performance based on industry standards.



Technical Information

	WATER ABSORPTION	ANSI / ISO - (%)	< 0.1%					
	ABRASION RESISTANCE	ANSI / ISO	GLOSS <140mm³	EDGED <140mm³	NATURAL <120mm³	ANTIQUED <120mm³	GRAINED <120mm³	
	BREAKING STRENGTH	ANSI - (lbf) ISO - (N)	6 mm ≥310 ≥1500		9 mm ≥570 ≥2600		20 mm PAVER ≥2925 ≥13000	
	SHADE VARIATION		Siena Bronze, Fresco, Noble V1	V2	Snow Veil, Corchia Pearl, Imperial White, Titanium Noir, Soil, Platinum Travertine V3			
	SLIP RESISTANCE	ANSI DCOF (WET) ISO - R VALUE	GLOSS: >0.50 DRY (ID) GLOSS R (-)	EDGED: >0.45 DRY (ID) EDGED R (-) <i>Majesto</i>	*EDGED: >0.50 DRY (ID) EDGED R (-)	NATURAL ≥0.60 (ID, IW, IW+, EW*, O/G*) NATURAL R10	ANTIQUED ≥0.75 (ID, IW, IW+, EW*, O/G*) ANTIQUED R11	GRAINED ≥0.75 (ID, IW, IW+, EW*, O/G*) GRAINED R11
	CHEMICAL RESISTANCE	ANSI / ISO	GLOSS CLASS A / MIN. CLASS B	EDGED CLASS A / MIN. CLASS B	NATURAL CLASS A	ANTIQUED CLASS A	GRAINED CLASS A	
	STAIN RESISTANCE	ANSI / ISO	GLOSS CLASS A / CLASS 4	EDGED CLASS A / CLASS 4	NATURAL CLASS A / CLASS 5	ANTIQUED CLASS A / CLASS 5	GRAINED CLASS A / CLASS 5	
	FROST RESISTANCE	ANSI / ISO	PASS					

*COLORS: Platinum Travertine

Test values are based on ANSI / ISO standards according to: ANSI A137.1 - Impervious (Porcelain) P1 Class,
ISO 13006 - G - B1_g Group, En 14411 - G - B1_g Group. Variances in test values can occur in different production lots.

Usage recommendation

Anatolia's recommendations for suitable applications.

<i>Usage Recommendations*</i>		GLOSS		EDGED		NATURAL		ANTIQUED		GRAINED		ANTIQUED PAVER		GRAINED PAVER	
APPLICATION		WALL	FLOOR	WALL	FLOOR	WALL	FLOOR	WALL	FLOOR	WALL	FLOOR	WALL	FLOOR	WALL	FLOOR
INTERIOR	RESIDENTIAL	•	ID	•	ID	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*		ID, IW, IW+, EW*, O/G*		ID, IW, IW+, EW*, O/G*
	COMMERCIAL	•	ID	•	ID	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*		ID, IW, IW+, EW*, O/G*		ID, IW, IW+, EW*, O/G*
	HEAVY COMMERCIAL	•		•		•		•		•		•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*
EXTERIOR	RESIDENTIAL / COMMERCIAL	•		•		•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*	•	ID, IW, IW+, EW*, O/G*

* These are Anatolia recommendations for suitable applications. They are not defined by ANSI / ISO Standards.
DCOF Classifications per ANSI A326.3: (ID): Interior, Dry (IW): Interior, Wet (IW+): Interior, Wet Plus (EW): Exterior, Wet (O/G): Oils/Greases

MORE INFO:

Town & Country Surfaces

230 Fifth Avenue
Suite 1714
New York NY 10001

General Inquiries:

info@tncsurfaces.com
Phone: 212-679-0312

